

## CLAIMS

1. A method of providing a substrate with viscous  
5 medium, comprising the steps of:  
    applying the viscous medium onto the substrate;  
    inspecting the results of said application;  
    determining errors of the application based on said  
inspection; and  
10      correcting at least some of said errors.
2. The method as claimed in claim 1, wherein the  
step of determining errors comprises the step of evaluat-  
ing all of the determined errors and deciding to what ex-  
15 tent the determined errors shall be corrected.
3. The method according to claim 1, wherein the step  
of determining errors further comprises the step of  
evaluating each of the determined errors and deciding on  
20 proper corrective action.
4. The method according to claim 3, wherein the step  
of determining errors comprises the steps of:  
    estimating for each of the determined errors the  
25 time required for performing said corrective action; and  
    calculating the overall time required for corrective  
action of all determined errors.
5. The method according to claim 1, wherein said  
30 correction comprises jetting of additional viscous medium  
onto the substrate and/or removing viscous medium from  
the substrate.
6. The method according to claim 5, wherein the step  
35 of correcting comprises the step of removing viscous me-  
dium from positions on the substrate where viscous medium  
has been unintentionally applied.

7. The method according to claim 5, wherein the step of correcting comprises the step of removing surplus viscous medium from positions on the substrate where more  
5 viscous medium has been applied than intended.

8. The method according to claim 5, wherein the step of correcting comprises the step of jetting of additional viscous medium to positions on the substrate where no  
10 viscous medium has been applied even though intended.

9. The method according to claim 5, wherein the step of correcting comprises the step of jetting of additional viscous medium to positions on the substrate where the  
15 amount of applied viscous medium is insufficient.

10. The method according to claim 8 or 9, further comprising the steps of:

inspecting the results of said jetting of additional  
20 viscous medium;

determining errors of said jetting of additional viscous medium based on said inspection; and

correcting at least some of said errors.

25 11. The method according to claim 1, wherein the step of applying viscous medium is performed by jetting.

12. The method according to claim 5, wherein the step of applying viscous medium is performed by jetting  
30 and wherein the application of the viscous medium and the jetting of additional viscous medium is performed by a single jetting device.

13. The method according to claim 1, wherein the  
35 step of applying viscous medium is performed by screen printing.

14. The method according to claim 1, wherein the step of applying viscous medium is performed by contact dispensing.

5        15. The method according to claim 1, wherein said step of correcting is performed after said step of applying viscous medium has been completed.

10       16. The method according to claim 1, wherein said step of inspecting is performed after said step of applying viscous medium has been completed.

15       17. The method according to claim 1, wherein said step of inspecting and said step of correcting are performed simultaneously after said step of applying viscous medium.

20       18. The method according to claim 1, wherein said step of correcting is performed simultaneously with said step of applying viscous medium.

25       19. The method according to claim 1, wherein said step of inspecting is performed simultaneously with said step of applying viscous medium.

30       20. An apparatus for providing a substrate with viscous medium, comprising:  
          application means for applying the viscous medium onto the substrate;  
          inspection means for inspecting the results of said application;  
          processing means for determining application errors based on said inspection; and  
          correction means for correcting at least some of  
 35       said errors.

21. The apparatus according to claim 20, wherein the processing means comprises evaluating means for evaluating each of the determined errors and deciding to what extent the determined errors shall be corrected.

5

22. The apparatus according to claim 20 or 21, wherein said correction means comprises jetting means for jetting of additional viscous medium onto the substrate and/or removing means for removing surplus viscous medium from the substrate.

10

23. The apparatus according to claim 20, wherein said application means is a jetting means.

15

24. The apparatus according to claim 20, wherein said application means is a jetting means and wherein said application means and said jetting means for jetting of additional viscous medium is the same jetting means.

20

25. The apparatus according to claim 20, wherein said application means is a screen printing means.

25

26. The apparatus according to claim 20, wherein said application means is a contact dispensing means.

27. An apparatus for correcting application errors in connection with application of viscous medium on a substrate, said apparatus comprising:

processing means adapted to receive information of said errors in the application of said viscous medium; and

30

correction means for correcting at least some of said errors based on said information.

35

28. The apparatus according to claim 27, further comprising inspection means for inspecting the results of

said application, wherein said processing means receives said information from said inspection means.

29. The apparatus according to claim 27, wherein the  
5 processing means comprises evaluating means for evaluating each of the determined errors.

30. The apparatus according to claim 27, wherein  
said correction means comprises jetting means for jetting  
10 of additional viscous medium onto the substrate and/or removing means for removing surplus viscous medium from the substrate.

31. A method of correcting application errors in regard to viscous medium provided on a substrate, comprising the steps of:

providing a jetting device; and  
using said jetting device for correcting said errors.

20

32. An apparatus for providing a substrate with viscous medium, comprising:

an applicator for applying the viscous medium onto the substrate;

25 an inspection device for inspecting the results of said application;

a processor for determining application errors based on said inspection; and

30 a correction device for correcting at least some of said errors.

33. The apparatus according to claim 32, wherein the processor is arranged for evaluating each of the determined errors and deciding to what extent the determined  
35 errors shall be corrected.

34. The apparatus according to claim 32, wherein said correction device comprises a jetting device for jetting of additional viscous medium onto the substrate.

5        35. The apparatus according to claim 32 or 33, wherein said correction device comprises a removing device for removing surplus viscous medium from the substrate.

10       36. The apparatus according to claim 32, wherein said applicator is a jetting device.

15       37. The apparatus according to claim 32, wherein said applicator is a jetting device and wherein said applicator and said jetting device for jetting of additional viscous medium is a single jetting device.

20       38. The apparatus according to claim 32, wherein said applicator is a screen printer.

20       39. The apparatus according to claim 32, wherein said applicator is a contact dispenser.

25       40. An apparatus for correcting application errors in connection with application of a viscous medium on a substrate, said apparatus comprising:

30       a processor adapted to receive information of said errors in the application of said viscous medium; and  
      a correction device for correcting at least some of said errors based on said information.

35       41. The apparatus according to claim 40, further comprising an inspection device for inspecting the results of said application, wherein said processor receives said information from said inspection device.

42. The apparatus according to claim 40, wherein the processor is arranged for evaluating each of the determined errors.

5        43. The apparatus according to claim 40, wherein said correction device comprises a jetting device for jetting of additional viscous medium onto the substrate.

10       44. The apparatus according to claim 40 or 43, wherein said correction device comprises a removing device for removing surplus viscous medium from the substrate.

FOI#01-07-0660